8CH H.264 Network DVR   AAG-DVR-318

Features:
Use the standard H.264 video compression format stream lower,high quality,longer recording time, taking up less bandwidth resources
GUI OSD interface,USB Mouse controller,more intuitive,easier to use for user-friendly
Support D1、HD1、CIF recording resolution，6 image quality adjustable
Hexaplex operation simultaneously:Preview,recording,playback,and network live,backup,playback
Multiple record mode:Auto、timer、motion recording mode
Recording playback support:Normal play、Speed play、Fast back play、Manual single-frame slow play
8CH Video input, 1CH Video output , 1CH Audio input , 1CH Audio output
Support drag the progress bar can be targeted playback time directly
Support Multiple channel playback at the same time(Support 8CH playback simultaneously)
Support Network function:one IE browser centralized monitoring and SNS Software for multiple DVR (up to 20 DVR simultaneously)
Support DHCP,DDNS,PPPoE and NTP network service
Supports remote surveillance up to 10 users simultaneously via the Enternet Explorer web browser
Support more than 17 kinds protocol of the PTZ control
Supports Multiple backup mode:USB flash drive and network backup
Support pre-alarm recording (before 10 sec),not lose any suspicious screen
Support 1 SATA HDD,unlimited for the capacity
Support remote view by Mobilephone，Support IR remoter controller
System auto recovery to power after power reconnected,and return to the pre-power-down state

Specifications:	
Item	**AAG-DVR-318**
Video Compression Format	H.264
Video System	NTSC / PAL
GUI OSD	YES
Video Input(BNC)	8CH (2CH D1 + 6CH CIF)
Video Output(BNC)	1CH BNC output
Audio Input/Output	1CH audio input,1CH audio output(RCA)
Maximum Recording Rate(CIF/HD1/D1)	CIF:352×240 pixels with 120 IPS <NTSC> /352×288 pixels with 100 IPS <PAL> **HD1:**704×240 pixels with 104 IPS <NTSC> /704×288 pixels with 88 IPS <PAL> **D1 :** 704×480 pixels with 52 IPS <NTSC> /704×576 pixels with 44 IPS <PAL>
Image Quality Setting	Supper Best,Well,Good,Medium,Normal and Bad
Hard Disk Storage	Support one SATA HDD,unlimited for the capacity
Alarm Input/Output	No
Multiplex Operation	Live display/record/playback/backup/network transmit
Recording Mode	Manual/Timer/Motion
Playback Mode	Multiple slow and rapid play speeds,manual and single-frame play modes,and support of drag the sliding bar to set.
Backup Device	USB flash disk / Network
Pre-alarm Recording	Recording for 10 seconds before alarming
Network Protocol	TCP/IP、PPPOE 、DDNS and NTP
Ethernet remote view	Support remote surveillance up to 10 users simultaneously
CMS software	YES
Mobilephone View	YES
VGA Interface	**VGA output**
Log record function	YES
Image Tour	YES
IR Remote control	YES
Video Loss Detection	YES
Video Adjustable	Hue /Saturation /Contrast /Brightness adjust
PTZ Control	YES,built-in RS-485 port
USB Mouse	YES
Power Source	DC 12V 3A
Key Lock(Password Protection)	YES
Power-down recovery function	YES
Size(mm)	259(W) x 221(D)x 46(H)
Weight	1.65KG (6pcs/carton)